

PRODUCT TYPE	NAME	15/07/2014
Glazed Ceramics	<b>ISLAND</b> <i>series</i>	
TECHNICAL SPECIFICATION		

### Technical Features

- glazed ceramic & ( glazed porcelain available in 10x10 only)
- 2 colours (limited to selected formats)
- 2 surfaces: gloss & satin
- 3 tile sizes
- natural stone look

### Colour



Hamilton



Hayman


### Format

#### Floor




33x33

#### Wall



33x50

#### Mosaics



glazed porcelain  
30x30 (sheeted)  
10x10 (tile size)

MANUFACTURER	DISTRIBUTOR	
	Prestige Tiles Pty Ltd 16 Raglan Road Auburn NSW 2144 p 8717 9044 f 8717 9017 www.prestigetiles.com	<b>1</b>

PRODUCT TYPE	NAME	15/07/2014
--------------	------	------------

Glazed Ceramics	<b>ISLAND</b> <i>series</i>	
-----------------	-----------------------------	--

TECHNICAL SPECIFICATION		
-------------------------	--	--

**TECHNICAL SPECIFICATIONS**

MODEL:	ISLAND	TYPE OF PRODUCT:	RED BODY CERAMIC TILE
NOMINAL SIZE:	33 x 33 & 33 x 50 cm (Unrectified)	NATURE OF SURFACE:	GLAZED
THICKNESS:	8.8 mm	BODY GROUP:	BIII
REF. STANDARD:			

TEST DESCRIPTION	STANDARD TEST METHOD	STANDARD REQUIREMENTS ISO 13006: EN 14411	R.A.K. CERAMICS SPECIFICATION
LENGTH & WIDTH	BS EN ISO 10545-2	±0.6 %	±0.25 %
THICKNESS	BS EN ISO 10545-2	±5.0 %	±5.0 %
STRAIGHTNESS OF SIDES	BS EN ISO 10545-2	±0.5 %	±0.3 %
RECTANGULARITY	BS EN ISO 10545-2	±0.6 %	±0.4 %
SURFACE FLATNESS	BS EN ISO 10545-2	±0.5 %	±0.25 %
WATER ABSORPTION	BS EN ISO 10545-3	≤0.5 %	≥10% - ≤16%
BREAKING STRENGTH	BS EN ISO 10545-4	≥1300 N	≥700 N
MODULUS OF RUPTURE	BS EN ISO 10545-4	≥35N/ mm <sup>2</sup>	≥18 N/mm <sup>2</sup>
RESISTANCE TO SURFACE ABRASION	BS EN ISO 10545-6	Manufacturer to state abrasion class	PEI Class 3
COEFFICIENT OF LINEAR THERMAL EXPANSION	BS EN ISO 10545-8	Test method available	≤7X10% C
THERMAL SHOCK RESISTANCE	BS EN ISO 10545-9	Test method available	No visible defect
CRAZING RESISTANCE	BS EN ISO 10545-11	Required	No Crazing
FROST RESISTANCE	BS EN ISO 10545-12	Required	-
RESISTANCE TO HOUSEHOLD CHEMICALS & SWIMMING POOL SALTS	BS EN ISO 10545-13	Minimum GB	Class GA No visible effect
RESISTANCE TO LOW CONCENTRATIONS ACIDS & ALKALIS	BS EN ISO 10545-13	Manufacturer to state classification	Class GLA No visible effect
RESISTANCE TO STAINING	BS EN ISO 10545-14	Minimum Class 3	Min. Class 5 Stain removed
SLIP RESISTANCE BY PENDULUM TEST (UK)	BS 7976	-	-

NOTE: This Technical Specification is applicable only to tiles in Choice **A**

MANUFACTURER	DISTRIBUTOR
--------------	-------------



Prestige Tiles Pty Ltd  
 16 Raglan Road  
 Auburn NSW 2144  
 p 8717 9044  
 f 8717 9017  
 www.prestigetiles.com