

Technical Information / Informacion Technicales
ISO 13006-10545/98 Class / Categoria B1a

0	Test item Producto de ensayo	Unit Unidad	Requirements of Standard Requisitos de la norma		Test result Resultado de la prueba
1	Dimensional variation Dimensionales	%	Length of side Longitud del lado	± 0.5	< 0.04
2	Side straightness Rectitud de los lados	%	± 0.5		< 0.5
3	Rectangularity Descuadre	%	± 0.5		< 0.5
4	Surface flatness Planitud superficial	%	Thickness variation Variation del espesor	± 0.5	< 0.5
			Warping degree Grado distorsion	± 0.5	< 0.5
			Side curvature Curvarura lateral	± 0.5	< 0.5
5	Surface quality Calidad de la superficie	-	0.8m From above no defects observed on 95% of tile / 0.8m Desde arriba no hay defectos observados en el 95% de azulejo		Conformed Conformado
6	Water absorption Absorcion de agua	(%)	Average value ≤ 0.5		< 0.32
7	Breaking strength Resistencia a la rotura	N/mm²	When thickness ≥ 7.5mm Average value ≥ 1300		2246
8	Rupture modulus Modulo de la ruptura	Ma	Average value / Valor medio ≥ 35 Individual value / Valor individual ≥ 32		> 35 > 32
9	Abrasion resistance Resistencia a la abrasion	mm³	≥ 175		> 175
10	Scratch resistance Resistencia al rayado	MOH	≥ 6		> 6
11	Frost resistance Resistencia a las heladas	-	No cracking after test No se agrieta despues de la prueba		Conformed Conformado
12	Resistance to acids & alkalis / Resistencia al acido y alcali	-	Not less than grade GB / UB No menos de grado GB / UB		GA / UA
13	Chemical resistance Resistencia quimica	-	Not less than grade GB / UB No menos de grado GB / UB		GA / UA

KREM

www.krem.co
www.linkinternationalkl.com

VECCHIO




Italian ink-jet design / Diseño de chorro de tinta Italiana

KREM

KREM VECCHIO

Gold



Size / Tamaño: 60 x 60cm

Packaging / Embalaje: 600 x 600mm x10mm	4pcs. / ctn.	1.44m2 / ctn.	31kg / ctn.	1,1 x 1,1m pallet: 40ctn. / pallet	57.6m2 / pallet
--	--------------	---------------	-------------	------------------------------------	-----------------